
J-82

Facial Recognition Terminal

Face / IC card / Password / Visitor QR code verification.



10,000 / 5,000

Users / Faces

200,000

Records

800 x 1024 HD display

High-definition display

TCP/IP

Verification methods

Face / IC card / Password / Visitor QR code

Communication

TCP/IP (optional Wi-Fi / 4G)

Control outputs

Wiegand, relay

Dimensions

248 mm x 134 mm x 24 mm

Specifications

J-82 | Facial Recognition Terminal

General	
Operating System	Linux
Camera	Dual-camera with 2 million pixels
Screen	800 x 1024 high-definition display screen
Touch Panel	Capacitive touchscreen
Language	Simplified Chinese, English
Power Supply	DC12V/2A
Operating Temperature & Humidity	-30 to 60 deg C; 10-90% RH
Dimensions	248 mm x 134 mm x 24 mm
Protection Rating	IP65 waterproof and dustproof
Identification	
Liveness Detection	Dual-camera liveness detection
Recognition Speed	<0.5s
Verification Methods	Face / IC card / Password / Visitor QR code
Card Reading	Standard IC card reader
Attendance	U-disk attendance, software attendance
Capacity	
User Capacity	10,000
Face Capacity	5,000
Fingerprint Capacity	5,000
Card Capacity	10,000
Password Capacity	10,000
Record Capacity	200,000
Communication and Interfaces	
External Interfaces	Wiegand output (26/34), relay output, exit button, doorbell
Communication Method	TCP/IP (optional Wi-Fi / 4G)
Output Method	Wiegand, relay
Input Method	Door open button