JF-45S

Facial Recognition Terminal

Face/Card/Password/Fingerprint/QR Code verification.



5,000

Faces

200,000

Records

4-inch HD display

IP65

Verification methods

Face/Card/Password/Fingerprint/QR Code

Communication

USB Flash Drive/TCP/IP (Optional Wi-Fi/4G)

Biometric capacity

5,000 fingerprints.

Dimensions

120mm*120mm*23mm

victorliu@fusworth.com
www.fusworth.com
+86 188 2005 8250

Specifications

JF-45S | Facial Recognition Terminal

General	
Operating System	Linux
Camera	: RGB+IR 2 MP
Screen	4-inch HD display
Touch Panel	Capacitive touchscreen
Language	Simplified Chinese, English
Power Supply	DC12V/2A
Operating Temperature & Humidity	-30 to 60 deg C; 10-90% RH
Dimensions	120mm*120mm*23mm
Protection Rating	IP65 waterproof and dustproof
Housing Material	Flame-retardant ABS plastic
Identification	
Liveness Detection	Dual-camera liveness detection
Recognition Speed	<0.5s
Verification Methods	Face/Card/Password/Fingerprint/QR Code
Card Reading	Standard IC card reader
Capacity	
User Capacity	10,000
Face Capacity	5,000
Fingerprint Capacity	5,000
Card Capacity	10,000
Password Capacity	10,000
Record Capacity	200,000
Communication and Interfaces	
External Interfaces	Wiegand output (26/34), relay output, exit button, doorbell
Communication Method	USB Flash Drive/TCP/IP (Optional Wi-Fi/4G)