# JF-52A

## Facial Recognition Terminal

Face / IC card / Password / Fingerprint / Palmprint / Visitor QR code verification.




## 10,000 / 5,000

Users / Faces

## 200,000

Records

### 5-inch HD display

High-definition display

## TCP/IP

### Verification methods

Face / IC card / Password / Fingerprint / Palmprint / Visitor QR code

### Communication

U-disk / TCP/IP (optional Wi-Fi / 4G)

### Biometric capacity

5,000 fingerprints; 1000 palmprints.

### Dimensions

192 mm x 86 mm x 22 mm

# Specifications

JF-52A | Facial Recognition Terminal

| | |
|---|---|
| **General** | |
| Operating System | Linux |
| Camera | Dual-camera with 2 million pixels |
| Screen | 5-inch high-definition display |
| Touch Panel | Capacitive touchscreen |
| Language | Simplified Chinese, English |
| Power Supply | DC12V/2A |
| Operating Temperature & Humidity | -30 to 60 deg C; 10-90% RH |
| Dimensions | 192 mm x 86 mm x 22 mm |
| Protection Rating | IP65 waterproof and dustproof |
| **Identification** | |
| Liveness Detection | Dual-camera liveness detection |
| Recognition Speed | <0.5s |
| Verification Methods | Face / IC card / Password / Fingerprint / Palmprint / Visitor QR code |
| Card Reading | Standard IC card reader |
| Attendance | USB card report, software attendance |
| **Capacity** | |
| User Capacity | 10,000 |
| Face Capacity | 5,000 |
| Fingerprint Capacity | 5,000 |
| Palmprint Capacity | 1000 |
| Card Capacity | 10,000 |
| Password Capacity | 10,000 |
| Record Capacity | 200,000 |
| **Communication and Interfaces** | |
| External Interfaces | Wiegand output (26/34), relay output, exit button, doorbell |
| Communication Method | U-disk / TCP/IP (optional Wi-Fi / 4G) |
| Output Method | Wiegand, relay |
| Input Method | Door open button |