JF-72H

Facial Recognition Terminal

Face / Card / Password / Palm vein / QR code verification.



10,000 / 5,000

Users / Faces

200,000

Records

7-inch HD display

TCP/IP

Verification methods

Face / Card / Password / Palm vein / QR code

Communication

USB flash drive/TCP/IP (Wi-Fi/4G optional)

Biometric capacity

1,000 Palmprints; 1000 palm veins.

Dimensions

233 x 130 x 27.8 mm

Specifications

JF-72H | Facial Recognition Terminal

General	
Operating System	Linux
Camera	RGB+IR 2 MP
Screen	7-inch high-definition display
Touch Panel	Capacitive touchscreen
Language	Simplified Chinese, English
Power Supply	DC12V/2A
Operating Temperature & Humidity	-30 to 60 deg C; 10-90% RH
Dimensions	233 x 130 x 27.8 mm
Protection Rating	IP65 waterproof and dustproof
Identification	
Liveness Detection	Dual-camera liveness detection
Recognition Speed	<0.5s
Verification Methods	Face / Card / Password / Palm vein / QR code
Card Reading	Standard IC card reader
Attendance	USB card report
Capacity	
User Capacity	10,000
Face Capacity	5,000
Palmprint Capacity	1,000
Palm Vein Capacity	1000
Card Capacity	10,000
Password Capacity	10,000
Record Capacity	200,000
Communication and Interfaces	
External Interfaces	Wiegand output (26/34), relay output, Ethernet port, exit button, doorbell
Communication Method	USB flash drive/TCP/IP (Wi-Fi/4G optional)
Output Method	Wiegand, relay
Input Method	Door opening button, visitor QR code